

Date of compilation: 11/04/2019 Revised: 14/10/2019 Version: 3 (Replaced 2)

| .1 | Product identifier: Velox Spray Neutral | | | |
|-----|--|--|--|--|
| .2 | Relevant identified uses of the substance or mixture and uses advised against: | | | |
| | Relevant uses: Disinfectant cleaner. For professional user only. | | | |
| | Uses advised against: All uses not specified in this section or in section 7.3 | | | |
| 1.3 | Details of the supplier of the safety data sheet: | | | |
| | MEDISEPT Sp. z o.o. Konopnica 159c 21-030 Motycz - lubelskie - Polska Phone.: +48 81 535 22 92 g.gromadzki@medisept.pl https://medisept.pl/ | | | |
| 1.4 | Emergency telephone number: +48 81 535 22 92 at time: 8.00 a.m. – 4.00. p.m. 112 (general emergency number) | | | |

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Eye Irrit. 2: Eye irritation, Category 2, H319

Flam. Liq. 3: Flammable liquids, Category 3, H226

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:



Hazard statements:

Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Lig. 3: H226 - Flammable liquid and vapour

Precautionary statements:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P280: Wear protective gloves/protective clothing/eye protection/face protection P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P370+P378: In case of fire: Use ABC powder extinguisher to extinguish P403+P233: Store in a well-ventilated place. Keep container tightly closed P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively Other hazards:

2.3

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Solution based on solvents, alcohols and surfactants.

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:



Velox Spray Neutral

Date of compilation: 11/04/2019 R

Revised: 14/10/2019 Version: 3 (Replaced 2)

| | Identification | | Chemical name/Classification | | Concentr |
|-------------------------|--|--------------------------|--|-----------------|----------|
| | 64-17-5 | Ethanol ¹ | | Self-classified | |
| | 200-578-6 603-002-00-5 01-2119457610-43- XXXX | Regulation 1272/2008 | Eye Irrit. 2: H319; Flam. Liq. 2: H225 - Danger | () (*) | 50 - <7 |
| | 67-63-0 | Propan-2-ol ¹ | | ATP CLP00 | |
| EC: Index: REACH: | 200-661-7 603-117-00-0 01-2119457558-25- XXXX | Regulation 1272/2008 | Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger | | 2,5 - <1 |

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes to the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety data Sheet

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

In case of consumption, seek immediate medical assistance showing the SDS for the product.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.



Date of compilation: 11/04/2019

Version: 3 (Replaced 2)

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Revised: 14/10/2019

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

| | • |
|----------------|-----------|
| Minimum Temp.: | 5 °C |
| Maximum Temp.: | 25 °C |
| Maximum time: | 36 Months |

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

7.2

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace There are no occupational exposure limits for the substances contained in the product



Velox Spray Neutral

Date of compilation: 11/04/2019 Re

Revised: 14/10/2019 Version: 3 (Replaced 2)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

DNEL (Workers):

| | | Short exposure | | Long exposure | |
|----------------|------------|----------------|------------------------|-----------------------|----------------|
| Identification | Systemic | Local | Systemic | Local | |
| Ethanol | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 64-17-5 | Dermal | Non-applicable | Non-applicable | 343 mg/kg | Non-applicable |
| EC: 200-578-6 | Inhalation | Non-applicable | 1900 mg/m ³ | 950 mg/m³ | Non-applicable |
| Propan-2-ol | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 67-63-0 | Dermal | Non-applicable | Non-applicable | 888 mg/kg | Non-applicable |
| EC: 200-661-7 | Inhalation | Non-applicable | Non-applicable | 500 mg/m ³ | Non-applicable |

DNEL (General population):

| | | Short e | xposure | Long exposure | |
|----------------|------------|----------------|----------------|-----------------------|----------------|
| Identification | Systemic | Local | Systemic | Local | |
| Ethanol | Oral | Non-applicable | Non-applicable | 87 mg/kg | Non-applicable |
| CAS: 64-17-5 | Dermal | Non-applicable | Non-applicable | 206 mg/kg | Non-applicable |
| EC: 200-578-6 | Inhalation | Non-applicable | 950 mg/m³ | 114 mg/m ³ | Non-applicable |
| Propan-2-ol | Oral | Non-applicable | Non-applicable | 26 mg/kg | Non-applicable |
| CAS: 67-63-0 | Dermal | Non-applicable | Non-applicable | 319 mg/kg | Non-applicable |
| EC: 200-661-7 | Inhalation | Non-applicable | Non-applicable | 89 mg/m³ | Non-applicable |

PNEC:

| Identification | | | | |
|----------------|--------------|----------------|-------------------------|----------------|
| Ethanol | STP | 580 mg/L | Fresh water | 0,96 mg/L |
| CAS: 64-17-5 | Soil | Non-applicable | Marine water | 0,79 mg/L |
| EC: 200-578-6 | Intermittent | 2,75 mg/L | Sediment (Fresh water) | 3,6 mg/kg |
| | Oral | 720 g/kg | Sediment (Marine water) | Non-applicable |
| Propan-2-ol | STP | 2251 mg/L | Fresh water | 140,9 mg/L |
| CAS: 67-63-0 | Soil | 28 mg/kg | Marine water | 140,9 mg/L |
| EC: 200-661-7 | Intermittent | 140,9 mg/L | Sediment (Fresh water) | 552 mg/kg |
| | Oral | 0,16 g/kg | Sediment (Marine water) | 552 mg/kg |

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|------------------------------|--|-----------|--------------|--|
| Mandatory hand protection | Protective gloves against minor risks | CATI | | Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2003+A1:2009 and EN ISO 374-1:2016 |

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

D.- Ocular and facial protection



Velox Spray Neutral

| Kork clothing CAT I recommended, in accordance with the regin EN ISO 6529:2013, EN ISO 6530:2005, 13688:2013, EN 464:1994. F Additional emergency measures Emergency measure Standards Emergency measure Standards Emergency measure ANSI Z358-1 DIN 12 899 | TIO | N 8: EXPOSURE (| CONTROLS/H | LINGUN | | | | |
|---|---|---|---|---|---|---|----------------|--|
| Protection Producting gass against protection Ex 100 000201 EN 50 4007/2018 the manufacturer is instructione. Use if if risk of splashing. E.: Body protection Precedure to the pro- teorement of the protection Precedure to the pro- profession/industrial uses CE in the No 05 4007/2018 the manufacturer is instructione. Use if if risk of splashing. F.: Additional emergency measures Response working to the pro- profession/industrial uses CE in the No 05 4007/2018 Response to the pro- profession/industrial uses CE in the No 05 4007/2018 Environmental exposure controls: In accordance with the community Environment is splashed to avoid environment splashed to birective 2010/75/EU, this product has the following characteristics: No 26 400.25 g/L) Average carbon number: 2.08 Average carbon number: 2.06 Average carbon number: 2.08 Average carbon number: 2.08 Average carbon number: 2.08 Average carbon number: 2.08 Average carbon number: 2.06 Average molecular weight: 47.24 g/mol Envisional state at 20 °C: Colouriess Colour: | | Pictogram | PPE | | Labelling | CEN Standard | | Remarks |
| Pretogram PPE Labelling CEN Standard Replace before any evidence of deteriors periodes of prolonged deteriors periodes of prolonged deteriors of prolonged deteriors of prolonged deteriors of prolonged deteriors F. Additional emergency measures Emergency measure Standards Emergency measure Standards Energency measure Standards Emergency measure Standards Emergency measure Standards Energency measure Standards Emergency measure Standards Emergency measure Standards Energency measure Standards Emergency measure Standards Energency measure Standards Energency measure Standards Emergency measure Standards Energency measure Standards Energency measure Avail 2359-1 IV Standards Energency measure Standards Energency measure Avail 2359-1 IV Standards Energency measure Standards Energency measure Avail 200 Standards Energency measure Standards Standards Intergency measure Avail 200 Standards IV <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>nanufacturer's instructions. Use if there</td> | | | | | | | | nanufacturer's instructions. Use if there |
| Image: Control of the product of the protection of the environment it is recommended. In accordance with the community legislation for the protection of the environment it is recommended. In accordance with the community legislation for the protection of the environment it is recommended. In accordance with the community legislation for the protection of the environment it is recommended to avoid environment it is recommended. In accordance with the community legislation for the protection of the environment it is recommended to avoid enviton avoid environment it is recommended to avoid environment it is | E | Body protection | | | | | | |
| Work clothing See Definition Definition Periods of prolonging desposure to the professional/mutatrial users CE III profesiIII profession | | Pictogram | PPE | | Labelling | CEN Standard | | |
| Image of both the product and its community legislation for the protection of the environment it is recommended to avoid environment gailage of both the product and its container. For additional information see subsection 7.1.D Div 12 899 Volatile organic compounds: With regard to Directive 2010/75/EU, this product has the following characteristics: V.O.C. (Supply): 68,6 % weight V.O.C. (Supply): 68,6 % weight V.O.C. (Supply): 68,6 % weight V.O.C. density at 20 °C: 600,25 g/L) Average molecular weight: 47,24 g/mol TION 9: PHYSICAL AND CHEMICAL PROPERTIES Information on basic physical and chemical properties: For complete information see the product datasheet. Appearance: Physical state at 20 °C: Liquid Appearance: Fluid Odour: Colourless Odour: Characteristic Odour threshold: Non-applicable * Valitility: Boling point at atmospheric pressure: 84 °C Vapour pressure at 20 °C: 20661,62 Pa (20,66 kPa) Vapour pressure at 20 °C: 20661,62 Pa (20,66 kPa) Vapour pressure at 20 °C: 20661,62 Pa (20,66 kPa) <td></td> <td></td> <td></td> <td>iing</td> <td>CATI</td> <td></td> <td>perio recor</td> <td>ds of prolonged exposure to the produc professional/industrial users CE III is nmended, in accordance with the regula N ISO 6529:2013, EN ISO 6530:2005, EN</td> | | | | iing | CATI | | perio recor | ds of prolonged exposure to the produc professional/industrial users CE III is nmended, in accordance with the regula N ISO 6529:2013, EN ISO 6530:2005, EN |
| DIN 12 899 DIN 202 DIN 15 Colspan="2">DIN 202 DIN 15 Colspan="2">DIN 202 DIN 15 Colspan="2">DIN 202 DIN 15 Colspan="2">DIN 202 DIN 15 Colspan="2"DIN 15 Colspan="2"DIN 12 DIN 15 Colspan 20 Co | F | Additional emerge | ency measures | | | | | |
| Image: Arrisk 238-1 Image: Arrisk 238-1< | | Emergency mea | sure | St | tandards | Emergency me | asure | Standards |
| In accordance with the community legislation for the protection of the environment it is recommended to avoid environment spillage of both the product and its container. For additional information see subsection 7.1.D Volatile organic compounds: With regard to Directive 2010/75/EU, this product has the following characteristics: V.O.C. (Supply): 68,6 % weight V.O.C. density at 20 °C: 600,25 kg/m² (600,25 g/L) Average carbon number: 2,08 Average molecular weight: 47,24 g/mol TION 9: PHYSICAL AND CHEMICAL PROPERTIES Information on basic physical and chemical properties: For complete information see the product datasheet. Appearance: Physical state at 20 °C: Liquid Appearance: Fluid Colour: Colourless Odour: Colourless Odour: Colourless Odour: Colourless Odour: Characteristic Odour threshold: Non-applicable * Volatility: Bolling point at atmospheric pressure: 84 °C Vapour pressure at 20 °C: 4241 Pa Vapour pressure at 50 °C: 20661,62 Pa (20,66 kPa) Evaporation rate at 20 °C: Non-applicable * | | Emergency sho | | | | | ions | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:201 |
| For complete information see the product datasheet.Appearance:LiquidAppearance:FluidColour:ColourlessOdour:ColourlessOdour threshold:Non-applicable *Volatility:84 °CBoiling point at atmospheric pressure:84 °CVapour pressure at 20 °C:20661,62 Pa (20,66 kPa)Vapour pressure at 20 °C:Non-applicable *Product description:Non-applicable * | Wi | V.O.C. (Supply): V.O.C. density at 2 Average carbon n | ve 2010/75/EU 20 °C: umber: | 68,6 600,2 2,08 | % weight 25 kg/m³ (600,2 | owing characteristics: | | |
| Appearance:LiquidPhysical state at 20 °C:LiquidAppearance:FluidColour:ColourlessOdour:ColourlessOdour:CharacteristicOdour threshold:Non-applicable *Volatility:Soling point at atmospheric pressure:Boiling point at atmospheric pressure:84 °CVapour pressure at 20 °C:20661,62 Pa (20,66 kPa)Vapour pressure at 20 °C:Non-applicable *Froduct description:Non-applicable * | | V.O.C. (Supply): V.O.C. density at 2 Average carbon n Average molecula | ve 2010/75/EU 20 °C: umber: ır weight: | 68,6 600,2 2,08 47,24 | % weight 25 kg/m³ (600,; 4 g/mol | owing characteristics: | | |
| Physical state at 20 °C:LiquidAppearance:FluidColour:ColourlessOdour:ColourlessOdour:CharacteristicOdour threshold:Non-applicable *Volatility:Soling point at atmospheric pressure:Boiling point at atmospheric pressure:84 °CVapour pressure at 20 °C:20661,62 Pa (20,66 kPa)Evaporation rate at 20 °C:Non-applicable *Froduct description:Von-applicable * | 10ITC | V.O.C. (Supply): V.O.C. density at 2 Average carbon n Average molecula N 9: PHYSICAL A | ve 2010/75/EU 20 °C: umber: r weight: ND CHEMIC physical and cl | 68,6 600,2 2,08 47,24 AL PRO | % weight 25 kg/m³ (600, 4 g/mol PERTIES properties: | owing characteristics: | | |
| Appearance:FluidColour:ColourlessOdour:CharacteristicOdour threshold:Non-applicable *Volatility:Volatility:Boiling point at atmospheric pressure:84 °CVapour pressure at 20 °C:4241 PaVapour pressure at 50 °C:20661,62 Pa (20,66 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:Von-applicable * | CTION Inf Fo | V.O.C. (Supply): V.O.C. density at 2 Average carbon no Average molecula N 9: PHYSICAL A formation on basic | ve 2010/75/EU 20 °C: umber: r weight: ND CHEMIC physical and cl | 68,6 600,2 2,08 47,24 AL PRO | % weight 25 kg/m³ (600, 4 g/mol PERTIES properties: | owing characteristics: | | |
| Colour:ColourlessOdour:CharacteristicOdour threshold:Non-applicable *Volatility:84 °CBoiling point at atmospheric pressure:84 °CVapour pressure at 20 °C:4241 PaVapour pressure at 50 °C:20661,62 Pa (20,66 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:Von-applicable * | TIOI Inf Fo Ap | V.O.C. (Supply): V.O.C. density at 2 Average carbon no Average molecula N 9: PHYSICAL A formation on basic or complete information opearance: | ve 2010/75/EU 20 °C: umber: ir weight: ND CHEMIC physical and cl tion see the pro | 68,6 600,2 2,08 47,24 AL PRO | % weight 25 kg/m³ (600, 4 g/mol PERTIES properties: asheet. | owing characteristics: 25 g/L) | | |
| Odour:CharacteristicOdour threshold:Non-applicable *Volatility:Volatility:Boiling point at atmospheric pressure:84 °CVapour pressure at 20 °C:4241 PaVapour pressure at 50 °C:20661,62 Pa (20,66 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:Von-applicable * | TIOI Inf Fo Ap Ph | V.O.C. (Supply): V.O.C. density at 2 Average carbon no Average molecula N 9: PHYSICAL A formation on basic or complete information opearance: hysical state at 20 ° | ve 2010/75/EU 20 °C: umber: ir weight: ND CHEMIC physical and cl tion see the pro | 68,6 600,2 2,08 47,24 AL PRO | % weight 25 kg/m ³ (600, 4 g/mol PERTIES properties: asheet. Liqu | owing characteristics: 25 g/L) | | |
| Odour threshold:Non-applicable *Volatility:Soling point at atmospheric pressure:84 °CVapour pressure at 20 °C:4241 PaVapour pressure at 50 °C:20661,62 Pa (20,66 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:Kon-applicable * | TIOI Inf Fo Ap Ph Ap | V.O.C. (Supply): V.O.C. density at 2 Average carbon no Average molecula N 9: PHYSICAL A formation on basic or complete information opearance: hysical state at 20 °C | ve 2010/75/EU 20 °C: umber: ir weight: ND CHEMIC physical and cl tion see the pro | 68,6 600,2 2,08 47,24 AL PRO | % weight 25 kg/m ³ (600, 4 g/mol PERTIES properties: asheet. Liqu Fluic | owing characteristics: 25 g/L) | | |
| Volatility:Boiling point at atmospheric pressure:84 °CVapour pressure at 20 °C:4241 PaVapour pressure at 50 °C:20661,62 Pa (20,66 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:Vanour pressure at 20 °C: | CTION Inf Fo Ap Ph Ap Co | V.O.C. (Supply): V.O.C. density at 2 Average carbon no Average molecula N 9: PHYSICAL A formation on basic or complete information opearance: hysical state at 20 % opearance: blour: | ve 2010/75/EU 20 °C: umber: ir weight: ND CHEMIC physical and cl tion see the pro | 68,6 600,2 2,08 47,24 AL PRO | % weight 25 kg/m³ (600, 4 g/mol PERTIES properties: asheet. Liqu Fluic Colo | owing characteristics: 25 g/L) id urless | | |
| Boiling point at atmospheric pressure:84 °CVapour pressure at 20 °C:4241 PaVapour pressure at 50 °C:20661,62 Pa (20,66 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:Vapour be a contract of the second | CTION Inf Fo Ap Ph Ap Co Od | V.O.C. (Supply): V.O.C. density at 2 Average carbon no Average molecula N 9: PHYSICAL A formation on basic or complete information opearance: hysical state at 20 % opearance: blour: dour: | ve 2010/75/EU 20 °C: umber: ir weight: ND CHEMIC physical and cl tion see the pro | 68,6 600,2 2,08 47,24 AL PRO | % weight 25 kg/m³ (600,2 4 g/mol PERTIES properties: asheet. Liqu Fluic Colo Chai | owing characteristics: 25 g/L) id iurless racteristic | | |
| Vapour pressure at 50 °C:20661,62 Pa (20,66 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:Image: Contemporation rate at 20 and the second sec | ETION Inf Fo Ph Ap Co Od Od | V.O.C. (Supply): V.O.C. density at 2 Average carbon no Average molecula N 9: PHYSICAL A formation on basic or complete information opearance: hysical state at 20 % opearance: blour: dour: dour threshold: | ve 2010/75/EU 20 °C: umber: ir weight: ND CHEMIC physical and cl tion see the pro | 68,6 600,2 2,08 47,24 AL PRO | % weight 25 kg/m³ (600,2 4 g/mol PERTIES properties: asheet. Liqu Fluic Colo Chai | owing characteristics: 25 g/L) id iurless racteristic | | |
| Evaporation rate at 20 °C: Non-applicable * Product description: | CTION Inf Fo App Ph App Co Od Od Vo | V.O.C. (Supply): V.O.C. density at 2 Average carbon no Average molecula N 9: PHYSICAL A formation on basic or complete information opearance: hysical state at 20 % opearance: blour: dour: dour: dour threshold: blatility: | ve 2010/75/EU, 20 °C: umber: ir weight: MD CHEMIC physical and cl tion see the pro | 68,6 600,2 2,08 47,24 AL PRO hemical p | % weight 25 kg/m³ (600,2 4 g/mol PERTIES properties: asheet. Liqu Fluic Colo Chai Non | owing characteristics: 25 g/L) id urless acteristic applicable * | | |
| Product description: | CTION Inf Fo Ap Ph Ap Co Od Od Od Od Bo | V.O.C. (Supply): V.O.C. density at 2 Average carbon m Average molecula N 9: PHYSICAL A formation on basic or complete information opearance: hysical state at 20 % opearance: holour: dour threshold: olatility: oiling point at atmos | ve 2010/75/EU 20 °C: umber: ur weight: ND CHEMIC physical and cl tion see the pro C: spheric pressur | 68,6 600,2 2,08 47,24 AL PRO hemical p | % weight 25 kg/m³ (600,2 4 g/mol PERTIES properties: asheet. Liqu Fluic Colo Chai Non 84 º | owing characteristics: 25 g/L) id urless acteristic applicable * | | |
| | CTION Inf Fo Ap Ph Ap Co Od Od Od Vo Bo Va | V.O.C. (Supply): V.O.C. density at 2 Average carbon no Average molecula N 9: PHYSICAL A formation on basic or complete information opearance: about: dour: dour: dour threshold: olatility: point at atmost apour pressure at 20 | ve 2010/75/EU, 20 °C: umber: ir weight: ND CHEMIC physical and cl tion see the pro C: c: | 68,6 600,2 2,08 47,24 AL PRO hemical p | % weight 25 kg/m³ (600,2 4 g/mol PERTIES properties: asheet. Liqu Fluic Colo Chai Non 84 º 424 | owing characteristics: 25 g/L) id urless racteristic rapplicable * | | |
| Density at 20 °C: 870 - 880 kg/m ³ | CTION Inf Fo Ap Ph Ap Co Od Od Od Od Vo Bo Va Va | V.O.C. (Supply): V.O.C. density at 2 Average carbon no Average molecula N 9: PHYSICAL A formation on basic or complete informator opearance: opearance: olour: dour: dour threshold: olatility: oiling point at atmost apour pressure at 20 apour pressure at 20 apour pressure at 20 | ve 2010/75/EU 20 °C: umber: ur weight: ND CHEMIC physical and cl tion see the pro C: C: spheric pressur 0 °C: 0 °C: | 68,6 600,2 2,08 47,24 AL PRO hemical p | % weight 25 kg/m³ (600,2 4 g/mol PERTIES properties: asheet. Liqu Fluic Colo Char Non 84 ° 424 | owing characteristics: 25 g/L) id iurless racteristic applicable * C I Pa 51,62 Pa (20,66 kPa) | | |
| - | TIOI Inf Fo Ph Ap Co Od Od Od Vo Bo Va Va Va Ev | V.O.C. (Supply): V.O.C. density at 2 Average carbon no Average molecula N 9: PHYSICAL A formation on basic or complete information opearance: appearance: abour: dour: dour: dour threshold: blatility: biling point at atmost apour pressure at 20 apour pressure at 20 apour pressure at 20 apour pressure at 20 apour pressure at 20 | ve 2010/75/EU 20 °C: umber: ur weight: ND CHEMIC physical and cl tion see the pro C: C: spheric pressur 0 °C: 0 °C: | 68,6 600,2 2,08 47,24 AL PRO hemical p | % weight 25 kg/m³ (600,2 4 g/mol PERTIES properties: asheet. Liqu Fluic Colo Chai Non 84 º 424 2066 Non | owing characteristics: 25 g/L) id urless racteristic rapplicable * C I Pa 51,62 Pa (20,66 kPa) rapplicable * | | |
| | TIOI Inf Fo Ap Ph Ap Co Od Od Od Vo Bo Va Ev Va Ev Ca De | V.O.C. (Supply): V.O.C. density at 2 Average carbon no Average molecula N 9: PHYSICAL A formation on basic or complete information opearance: about at the shold: about threshold: about threshold: about pressure at 20 apour pressure at 20 ap | ve 2010/75/EU 20 °C: umber: ur weight: ND CHEMIC physical and cl tion see the pro C: C: spheric pressur 0 °C: 0 °C: 0 °C: | 68,6 600,2 2,08 47,24 AL PRO hemical p | % weight 25 kg/m³ (600,2 4 g/mol PERTIES properties: asheet. Liqu Fluic Colo Chai Non 84 º 424 2066 Non | owing characteristics: 25 g/L) id urless racteristic rapplicable * C I Pa 51,62 Pa (20,66 kPa) rapplicable * | | |

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



| Date of compilation: 11/04/2019 Revised: 14/10/201 | 9 Version: 3 (Replaced 2) |
|--|--------------------------------------|
| SECTION 9: PHYSICAL AND CHEMICAL PROPER | RTIES (continued) |
| Kinematic viscosity at 20 °C: | 1,29 cSt |
| Kinematic viscosity at 40 °C: | Non-applicable * |
| Concentration: | Non-applicable * |
| pH: | 6,75 - 8,25 |
| Vapour density at 20 °C: | Non-applicable * |
| Partition coefficient n-octanol/water 20 °C: | Non-applicable * |
| Solubility in water at 20 °C: | Non-applicable * |
| Solubility properties: | Completely miscible |
| Decomposition temperature: | Non-applicable * |
| Melting point/freezing point: | Non-applicable * |
| Explosive properties: | Non-applicable * |
| Oxidising properties: | Non-applicable * |
| Flammability: | |
| Flash Point: | 23 °C |
| Flammability (solid, gas): | Non-applicable * |
| Autoignition temperature: | 399 °C |
| Lower flammability limit: | Not available |
| Upper flammability limit: | Not available |
| Explosive: | |
| Lower explosive limit: | Non-applicable * |
| Upper explosive limit: | Non-applicable * |
| 9.2 Other information: | |
| Surface tension at 20 °C: | Non-applicable * |
| Refraction index: | 1,364 - 1,368 |
| *Not relevant due to the nature of the product, not providing it | information property of its hazards. |

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

SECTION 10: STABILITY AND REACTIVITY

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable | Not applicable | Risk of combustion | Avoid direct impact | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.



| f co | compilation: 11/04/2019 | Revised: 14/10/2019 | Version: 3 (Repla | ced 2) | | | | | |
|------|--|---|---|---|--|------------------------|--|--|--|
| CTI | FION 11: TOXICOLOGICAL | INFORMATION | | | | | | | |
| | Information on toxicological effects: | | | | | | | | |
| | The experimental information related to the toxicological properties of the product itself is not available | | | | | | | | |
| | Dangerous health implication | - | | | | | | | |
| | In case of exposure that is re | In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure: | | | | | | | |
| | Acute toxicity : Based of as dangerous for consum Corrosivity/Irritability: B | | on see section 3. e classification crite | eria are not met, as | | | | | |
| | classified as dangerous fo B- Inhalation (acute effect): | Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. Inhalation (acute effect): | | | | | | | |
| | as dangerous for inhalation - Corrosivity/Irritability: B | on available data, the class on. For more information so Based on available data, the or this effect. For more info | ee section 3. e classification crite | eria are not met, as | | | | | |
| | C- Contact with the skin and | | | | | | | | |
| | classified as dangerous for | Based on available data, the or skin contact. For more ir Produces eye damage after icity. mutagenicity and toxic | nformation see sec r contact. | tion 3. | it does not contain sul | bstances | | | |
| | as dangerous for the effect IARC: Propan-2-ol (3) - Mutagenicity: Based on dangerous for this effect. - Reproductive toxicity: B | on available data, the class octs mentioned. For more in a available data, the classifi For more information see Based on available data, the or this effect. For more info | nformation see sect ication criteria are r section 3. e classification crite | ion 3. 1ot met, as it does 1ria are not met, as | not contain substance | s classified as | | | |
| | dangerous with sensitisin - Cutaneous: Based on a | available data, the classifica ng effects. For more inform available data, the classifica . For more information see city (STOT) - single exposu | ation see section 3 ation criteria are not section 3. | | | | | | |
| | Based on available data, t inhalation. For more inform G- Specific target organ toxic | | | er, it contains subst | tances classified as da | ngerous for | | | |
| | does not contain substan - Skin: Based on available | Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3. Aspiration hazard: | | | | | | | |
| | Based on available data, t this effect. For more infor Other information: | the classification criteria ar rmation see section 3. | re not met, as it doe | s not contain subs | tances classified as da | angerous for | | | |
| | Non-applicable | | | | | | | | |
| | Specific toxicology informati | ion on the substances: | | | | | | | |
| | | | | | | | | | |
| | | Identification | | | | Conus | | | |
| | Ethanol | Identification | | | te toxicity 6200 ma/ka | Genus Rat | | | |
| | Ethanol CAS: 64-17-5 | Identification | | Acu LD50 oral LD50 dermal | fe toxicity 6200 mg/kg 20000 mg/kg | Genus Rat Rabbit | | | |



Velox Spray Neutral

Date of compilation: 11/04/2019

Revised: 14/10/2019 Version: 3 (Replaced 2)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

| Identification | | Acute toxicity | Genus |
|----------------|-----------------|-------------------|-------|
| Propan-2-ol | LD50 oral | 5280 mg/kg | Rat |
| CAS: 67-63-0 | LD50 dermal | 12800 mg/kg | Rat |
| EC: 200-661-7 | LC50 inhalation | n 72,6 mg/L (4 h) | Rat |

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

| Identification | Acute toxicity | | Species | Genus |
|----------------|----------------|-------------------|-------------------------|------------|
| Ethanol | LC50 | 11000 mg/L (96 h) | Alburnus alburnus | Fish |
| CAS: 64-17-5 | | 9268 mg/L (48 h) | Daphnia magna | Crustacean |
| EC: 200-578-6 | EC50 | 1450 mg/L (192 h) | Microcystis aeruginosa | Algae |
| Propan-2-ol | LC50 | 9640 mg/L (96 h) | Pimephales promelas | Fish |
| CAS: 67-63-0 | EC50 | 13299 mg/L (48 h) | Daphnia magna | Crustacean |
| EC: 200-661-7 | EC50 | 1000 mg/L (72 h) | Scenedesmus subspicatus | Algae |

12.2 Persistence and degradability:

| Identification | Degr | adability | Biodegradability | |
|----------------|----------|----------------|------------------|----------|
| Ethanol | BOD5 | Non-applicable | Concentration | 100 mg/L |
| CAS: 64-17-5 | COD | Non-applicable | Period | 14 days |
| EC: 200-578-6 | BOD5/COD | 0.57 | % Biodegradable | 89 % |
| Propan-2-ol | BOD5 | 1.19 g O2/g | Concentration | 100 mg/L |
| CAS: 67-63-0 | COD | 2.23 g O2/g | Period | 14 days |
| EC: 200-661-7 | BOD5/COD | 0.53 | % Biodegradable | 86 % |

12.3 Bioaccumulative potential:

| Identification | Bioaccumulation potential | | |
|----------------|---------------------------|-------|--|
| Ethanol | BCF | 3 | |
| CAS: 64-17-5 | Pow Log | -0.31 | |
| EC: 200-578-6 | Potential | Low | |
| Propan-2-ol | BCF | 3 | |
| CAS: 67-63-0 | Pow Log | 0.05 | |
| EC: 200-661-7 | Potential | Low | |

12.4 Mobility in soil:

| Identification Absorption/ | | on/desorption | Volatility | |
|----------------------------|-----------------|----------------------|------------|--------------------|
| Ethanol | Кос | 1 | Henry | 4,61E-1 Pa∙m³/mol |
| CAS: 64-17-5 | Conclusion | Very High | Dry soil | Yes |
| EC: 200-578-6 | Surface tension | 2,339E-2 N/m (25 °C) | Moist soil | Yes |
| Propan-2-ol | Кос | 1.5 | Henry | 8,207E-1 Pa·m³/mol |
| CAS: 67-63-0 | Conclusion | Very High | Dry soil | Yes |
| EC: 200-661-7 | Surface tension | 2,24E-2 N/m (25 °C) | Moist soil | Yes |

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) | |
|-----------|--|---|--|
| 20 01 29* | detergents containing hazardous substances Dangerous | | |



Date of compilation: 11/04/2019 Revised: 14/10/2019

Version: 3 (Replaced 2)

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP4 Irritant - skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:

| • | 14.1 | UN number: | UN1987 |
|-------------------|---------|---|----------------------------|
| | 14.2 | UN proper shipping name: | ALCOHOLS, N.O.S. (Ethanol) |
| | 14.3 | Transport hazard class(es): | 3 |
| $\langle \rangle$ | | Labels: | 3 |
| | 14.4 | Packing group: | III |
| 3 | 14.5 | Environmental hazards: | No |
| • | 14.6 | Special precautions for user | |
| | | Special regulations: | 274, 601 |
| | | Tunnel restriction code: | D/E |
| | | Physico-Chemical properties: | see section 9 |
| | | Limited quantities: | 5 L |
| | 14.7 | Transport in bulk according to Annex II of Marpol and the IBC Code: | Non-applicable |
| Transport of da | ngerous | goods by sea: | |
| With regard to I | MDG 38- | -16: | |
| | 14.1 | UN number: | UN1987 |
| | 14.2 | UN proper shipping name: | ALCOHOLS, N.O.S. (Ethanol) |
| | 14.3 | Transport hazard class(es): | 3 |
| | | Labels: | 3 |
| | 14.4 | Packing group: | III |
| 2 | 14.5 | Environmental hazards: | No |
| | 14.6 | Special precautions for user | |
| | | Special regulations: | 223, 274 |
| | | EmS Codes: | F-E, S-D |
| | | Physico-Chemical properties: | see section 9 |
| | | Limited quantities: | 5 L |
| | | Segregation group: | Non-applicable |
| | 14.7 | Transport in bulk according to Annex II of Marpol and the IBC Code: | Non-applicable |
| Transport of da | ngerous | goods by air: | |
| With regard to IA | | 0.2010 | |



Velox Spray Neutral

| Date of compilation: 11/04/2 | 2019 | Revised: 14/10/2019 | Version: 3 (Replaced 2) |
|------------------------------|--------|---|----------------------------|
| SECTION 14: TRANSF | PORT I | NFORMATION (continued) | |
| | 14.1 | UN number: | UN1987 |
| She | 14.2 | UN proper shipping name: | ALCOHOLS, N.O.S. (Ethanol) |
| | 14.3 | Transport hazard class(es): | 3 |
| | | Labels: | 3 |
| 3 | 14.4 | Packing group: | III |
| • | 14.5 | Environmental hazards: | No |
| | 14.6 | Special precautions for user | |
| | | Physico-Chemical properties: | see section 9 |
| | 14.7 | Transport in bulk according to Annex II of Marpol and the IBC Code: | 11 |

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture: 15.1

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Ethanol (Product-type 1, 2, 4, 6) ; Propan-2-ol (Product-type 1, 2, 4)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable Seveso III:

| Section | Description | Lower-tier requirements | Upper-tier requirements |
|---------|-------------|----------------------------|----------------------------|
| P5c | | 5000 | 50000 |

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

- Regulation (EC) No 1223/2009 of the European Parliament and of the Council of 30 November 2009 on cosmetic products

- Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents
- Commission Regulation (EC) No 907/2006 of 20 June 2006 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes III and VII
- Commission Regulation (EC) No 551/2009 of 25 June 2009 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes V and VI thereto (surfactant derogation)

Chemical safety assessment: 15.2

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation

H226: Flammable liquid and vapour

Texts of the legislative phrases mentioned in section 3:



Velox Spray Neutral

| Date of compilation: 11/04/2019Revised: 14/10/2019Version: 3 (Replaced 2) |
|--|
| SECTION 16: OTHER INFORMATION (continued) |
| The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 CLP Regulation (EC) No 1272/2008 : |
| Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 2: H225 - Highly flammable liquid and vapour STOT SE 3: H336 - May cause drowsiness or dizziness |
| Classification procedure: |
| Eye Irrit. 2: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3) |
| Advice related to training: |
| Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. |
| Principal bibliographical sources: |
| http://echa.europa.eu http://eur-lex.europa.eu |
| Abbreviations and acronyms: |
| ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code |
| IATA: International Air Transport Association |
| ICAO: International Civil Aviation Organisation |
| COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand |
| BCE: Bioconcentration factor |
| LD50: Lethal Dose 50 |
| LC50: Lethal Concentration 50 |
| EC50: Effective concentration 50 |
| Log-POW: Octanol-water partition coefficient |
| Koc: Partition coefficient of organic carbon |

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.